



T-4150

T-4170

T-41100

T-41120

T-41150

T-41200

T-41250

T-41351

T-41500

**Theoretical Discharge Volume ( gpm)**

**Pump Speed (rpm)**

|                | PSI  | 200   | 250   | 300   | 350   | 400   | 450   | 500   | 550   | 600   |
|----------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>T-4150</b>  | 711  | 26.95 | 33.55 | 40.42 | 47.03 | 53.90 | 60.50 | 67.11 | 73.71 | 80.58 |
| <b>T-4170</b>  | 996  | 18.76 | 23.51 | 28.01 | 32.76 | 37.25 | 42.01 | 46.76 | 51.52 | 55.75 |
| <b>T-41100</b> | 1422 | 11.89 | 15.06 | 17.97 | 20.87 | 23.78 | 26.95 | 29.85 | 32.76 | 35.67 |
| <b>T-41120</b> | 1707 | 10.83 | 13.47 | 16.12 | 18.76 | 21.66 | 24.31 | 26.95 | 29.59 | 32.23 |
| <b>T-41150</b> | 2134 | 7.66  | 9.51  | 11.36 | 13.47 | 15.32 | 17.17 | 19.02 | 20.87 | 22.72 |
| <b>T-41200</b> | 2845 | 5.81  | 7.40  | 8.72  | 10.30 | 11.62 | 13.21 | 14.53 | 15.85 | 17.44 |
| <b>T-41250</b> | 3556 | 4.76  | 5.81  | 6.87  | 8.19  | 9.25  | 10.57 | 11.62 | 12.95 | 14.00 |
| <b>T-41351</b> | 4978 | 3.70  | 4.49  | 5.55  | 6.34  | 7.13  | 8.19  | 8.98  | 9.78  | 10.83 |
| <b>T-41500</b> | 7112 |       |       |       |       |       |       |       |       |       |

*Based on 100% Volumetric Efficiency*

